

PRODUCT-DETAILS

AL 500 N 32 HS

AL TIN 2HOLE NEMA STR LUG 400 32IN



General Information

Extended Product Type	AL 500 N 32 HS
Product ID	7TAA262020R0284
EAN	0783786016877
Catalog Description	AL TIN 2HOLE NEMA STR LUG 400 32IN
Long Description	Aluminum Two-Hole NEMA Lugs - straight lug, 477-500 kcmil and 500-600 Compact AL -CU and ACSR 397.5 (26/7) and 477 (18/1), installing dies 106A, 300, 317, 1 5/16, 14A, 15A. Length 32 inch. Pad 1-3/4 inch wide x 3-9/16 inch long x 29/64 inch thick. Barrel 27-5/8 inch long x 1-5/16 inch Outside Diameter. (2) 9/16 inch diameter holes on 1-3/4 inch centers. Oxide Inhibitor. Piink Cap. Includes Heat Shrink.

Ordering

EAN	0783786016877
UPC	783786016877
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	5 piece
Package Level 1 Width	8 in 203 mm
Package Level 1 Height	8 in 203 mm

Package Level 1 Depth / Length	40 in 1016 mm
--------------------------------	------------------

Additional Information

Application	General Purpose Lugs for Aluminum and Copper Terminations
Brand / Label	Homac
Connection Type	Compression
Effective Date	20100629
Insulation Material	None
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Compression Lug Two Hole
Size	32 inch long
Special Functions	Dual Rated for use with Aluminum and Copper Conductors. Prefilled with Oxide Inhibitor. Marked with Conductor Sizes and Die Reference. Meet or Exceed ANSI C119.4 Specifications.
Standards	ANSI C119.4
Wire Size	477 to 500 kcmil 500 to 600 kcmil

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	AL 500 N 32 HS
Instructions and Manuals	AL 500 N 32 HS

Classifications

UNSPSC	39121409
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4543 >> Wire connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Distribution Connectors

