

PRODUCT-DETAILS

# AL 500 N 608

## AL TIN 2HOLE NEMA STR LUG 500-600



### General Information

Extended Product Type	AL 500 N 608
Product ID	7TAA262020R0326
EAN	0075114161725
Catalog Description	AL TIN 2HOLE NEMA STR LUG 500-600
Long Description	Aluminum Two-Hole NEMA Lugs - straight lug, 477-500 kcmil and 500-600 Compact AL -CU and ACSR 397.5 (26/7) and 477 (18/1), installing dies 608, 786, 722, 936. Length 8-1/4 inch. Pad 1-3/4 inch wide x 3-9/16 inch long x 29/64 inch thick. Barrel 3-5/16 inch long x 1-1/2 inch Outside Diameter. (2) 9/16 inch diameter holes on 1-3/4 inch centers. Oxide Inhibitor. Piink Cap.

### Ordering

EAN	0075114161725
UPC	075114161725
Country of Origin	United States (US)
Customs Tariff Number	8536904000
Selling Unit of Measure	each

### Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	6.25 in 159 mm
Package Level 1 Height	7 in 178 mm

Package Level 1 Depth / Length	7.75 in 197 mm
--------------------------------	-------------------

---

## Additional Information

Application	General Purpose Lugs for Aluminum and Copper Terminations
Brand / Label	Homac
Connection Type	Compression
Effective Date	20140225
Insulation Material	None
Number of Batteries	0
Product Name	ALUMINUM LUG
Product Type	Compression Lug Two Hole
Size	8-1/4 inch long x 1-3/4 inch wide
Special Functions	Dual Rated for use with Aluminum and Copper Conductors. Prefilled with Oxide Inhibitor. Marked with Conductor Sizes and Die Reference. Meet or Exceed ANSI C119.4 Specifications.
Standards	ANSI C119.4
Wire Size	477 to 500 kcmil 500 to 600 kcmil

---

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	AL 500 N 608
Instructions and Manuals	AL 500 N 608

---

## Classifications

UNSPSC	39121409
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4543 >> Wire connectors

---

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Distribution Connectors

