

PRODUCT-DETAILS

AC 750 TN

Aluminum Comp Splice, 750 kcmil



General Information

Extended Product Type	AC 750 TN
Product ID	7TAA262050R0100
EAN	0783786691913
Catalog Description	Aluminum Comp Splice, 750 kcmil
Long Description	Tin Plated Aluminum Straight Splices, concentric 700-750 kcmil AL-CU, ACSR 636 (26/7) ACSR, installing dies 140H, 301, 342, 1 1/2. Length 8-9/32 inches, Diameter 1-39/64 inch. Bore Depth 4 inch. Oil Stop. Oxide Inhibitor, (2) Yellow Caps.

Ordering

EAN	0783786691913
UPC	783786691913
Country of Origin	United States (US)
Customs Tariff Number	8536904000
Selling Unit of Measure	each

Container Information

Package Level 1 Units	20 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth /	1 in

Length	25 mm
--------	-------

Additional Information

Application	Cable Splice
Brand / Label	Homac
Connection Type	Compression
Effective Date	20080619
Insulation Material	None
Number of Batteries	0
Number of Conductors	2
Product Name	ELECTRICAL SPLICE<1000V
Product Type	Compression Splice
Size	8-9/32 inch long
Special Functions	Dual Rated for Aluminum or Copper Conductors. Prefilled with Oxide Inhibiting Compound.
Standards	ANSI C119.4
Surface Finishing	Tin-Plated

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	AC 750 TN
Instructions and Manuals	AC 750 TN

Classifications

UNSPSC	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Distribution Connectors

