

PRODUCT-DETAILS

ATC 1000 R 500

AL TAPER REDUCE SPLICE 500-1000



General Information

Extended Product Type	ATC 1000 R 500
Product ID	7TAA262050R0172
EAN	0783786697052
Catalog Description	AL TAPER REDUCE SPLICE 500-1000
Long Description	Aluminum Tapered Reducing Splices, wire size 500 kcmil AL-CU to 954 - 1000 kcmil AL-CU. Installing Dies 161, 302, 292, 319. Length 9.7/8 inch, Outside Diameter 1-27/32. Oil Stop. Oxide Inhibitor. Pink Cap, Brown Cap.

Ordering

EAN	0783786697052
UPC	783786697052
Country of Origin	United States (US)
Customs Tariff Number	8536904000
Selling Unit of Measure	each

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth /	1 in

Length 25 mm

Additional Information

Application	Tapered ends enable use in High-Voltage Applications up to 69kV.
Brand / Label	Homac
Connection Type	Compression
Effective Date	20080619
Insulation Material	None
Number of Batteries	0
Number of Conductors	2
Product Name	ELECTRICAL SPLICE<1000V
Product Type	Compression Splice Tapered Reducer
Size	Length 9-7/8 inches
Special Functions	Dual-Rated. Use with aluminum and copper conductors. Solid Center Stop assures proper cable insertion, prevents moisture migration. Conductor bores coated with oxide inhibitor to prevent oxidation. All Splices marked with Die References for Easy Identification.
Standards	ANSI C119.4
Surface Finishing	Bare

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	ATC 1000 R 500
Instructions and Manuals	ATC 1000 R 500

Classifications

UNSPSC	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Distribution Connectors

