

PRODUCT-DETAILS

ATC 500 R 1/0 AL TAPER REDUCE SPLICE 1/0-500



General Information		
Extended Product Type	ATC 500 R 1/0	
Product ID	7TAA262050R0215	
EAN	0783786697489	
Catalog Description	AL TAPER REDUCE SPLICE 1/0-500	
Long Description	Aluminum Tapered Reducing Splices, wire size 500 kcmil AL-CU to 1/0 Stranded AL-CU. Installing Dies 106, 300, 317, 15A, 1 5/16. Length 5-9/16 inch, Outside Diameter 1-5/16 inch. Oil Stop. Oxide Inhibitor. Yellow Cap. Pink Cap.	

Ordering	
EAN	0783786697489
UPC	783786697489
Country of Origin	United States (US)
Customs Tariff Number	8536904000
Selling Unit of Measure	each

Container Information		
Package Level 1 Units	25 piece	
Package Level 1 Width	6.25 in	
	159 mm	
Package Level 1 Height	7 in	
	178 mm	
Package Level 1 Depth /	7.75 in	

Length 197 mm

Additional Information	
Application	Tapered ends enable use in High-Voltage Applications up to 69kV.
Brand / Label	Homac
Connection Type	Compression
Effective Date	20080619
Insulation Material	None
Number of Batteries	0
Number of Conductors	2
Product Name	ELECTRICAL SPLICE<1000V
Product Type	Compression Splice Tapered Reducer
Size	Length 5-5/8 inches
Special Functions	Dual-Rated. Use with aluminum and copper conductors. Solid Center Stop assures proper cable insertion, prevents moisture migration. Conductor bores coated with oxide inhibitor to prevent oxidation. All Splices marked with Die References for Easy Identification.
Standards	ANSI C119.4
Surface Finishing	Bare

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	ATC 500 R 1/0	
Instructions and Manuals	ATC 500 R 1/0	

Classifications		
UNSPSC	39121449	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Accessories\ and\ Apparatus \rightarrow Distribution\ Connectors$

